



A B C D E F

8 8

7 7

6 6

5 5

4 4

3 3

2 2

1 1

A B D E F

**Kinco**  
AC SERVO  
JD640

X9 24V MODE ▲ ▼ ENTER  
STOA+ STOA- STOB+ STOB- GND  
STO

X7 A B  
24VS GA  
GNDS AIN1  
COM1 AIN2  
DIN1 OUT1+  
DIN2 OUT1-  
DIN3 OUT2+  
DIN4 OUT2-  
COM2 OUT3  
DIN5 OUT4  
DIN6 OUT5  
DIN7 24VO  
DIN8 COM0  
OUT7+ OUT6+  
OUT7- OUT6-

X2 RS485

X4 CAN

X3 RS232

X1 ENCODER OUT

X5 MASTER ENCODER

X6 ENCODER IN



CHARGE

249

255

216

19.5

7.5

40

150

230

38.5

∅5.5

6

294

294

23.5

38.5

53.5

77

85.5

M4-PE

5.5

CAUTION  
小心



- Housing and heatsink may be hot!
- 驱动器散热器及外壳可能造成烧伤!

WARNING  
警告



- Hazardous voltage at all X8, X10 terminals!
- X8、X10 端子高压危险!
- Charge LED indicates hazardous voltage inside drive and all X8, X10 terminals.
- Wait at least 10 minutes after removing power supply!
- 红色发光二极管指示内部以及X8、X10 端子高压危险!
- 切断电源10分钟后再操作!

接地



- Must connect protective earth terminal (⊕) for protection against electric shock!
- 确保可靠接地，防止触电!

Serial number →

X10

RB+ RB- PE T S R

X8

PE W V U

		MATERIAL			<p style="text-align: center;"><b>Kinco</b></p>				
		SURFACE							
DIMENSIONS IN MM		GENERAL-TOLERANCE	ISO2768-MK		<p style="text-align: center;"><b>JD630-640-Assembly</b></p>				
STYLIST	Shane	20181017							
AUDITOR									
APPROVER					PARTNUMBER				
VERSION	MARK	DATE	NAME	LINEAR	TECHNOLOGY	SCALE	1:1	QUANTITY	WEIGHT